




SSL200 | Stainless Steel Miniature Lubricator

Specification and ordering

Symbol



Features

1. For high pressure use, corrosion and chemical resistance.
2. Good performance in chemically working environments and outdoor facility.
3. Suitable for semi-conductor industry.
4. Lubricator oil can be replenished without stopping air supply.
5. Oil spray in mist ensures good lubrication for machines.
6. Light weight, compact size for space saving.
7. CE and EX-proof certified.



II 2G Ex h IIC T4 Gb
II 2D Ex h IIC T135°C Db
-10 °C ≤ Ta ≤ 70 °C



*Lubricator oil (Recommended): ISO-VG32


How to order

SSL200	—	02	N
Stainless Steel SUS316 Miniature		Port size	Thread
Miniature Lubricator		02 : 1/4"	Blank : G N : NPT R : Rc

Specifications

Model	SSL200
Port size	1/4"
Fluid	Compressed air
Body material	Stainless steel SUS316
Bowl material	Stainless steel SUS316
Operating pressure range	0 ~ 20 kgf/cm ²
Max. inlet pressure	20 kgf/cm ²
Max. flow rate l/min (ANR)	2500
Ambient temperature	-10°C ~ 70°C
Lubricator bowl capacity	125cc
Proof pressure	40 kgf/cm ²
Net weight	1200g
Accessories	Mounting bracket set

Dimensions



Confirm the selected model, operating conditions and options with Fluidline before ordering.